



RJ-215 High Temperature Fluid Disabled Electric Detonator

Detonator Specifications:


Nominal Base Charge:	350mg RDX output charge
Initiating Charge:	150 mg Lead Azide, 100 mg RDX
Shell Material:	Aluminum
Shell Diameter:	0.288" (7.32mm) max
Shell Length:	1.673" (42.5mm) max
Plug:	Nitrilica™ (black)
Leg Wires:	1.21 feet length (0.40m) copper wire 22 gauge (0.57mm) Zitel™ red and purple insulated

Firing Specifications:

Temperature Rating:	340°F (170°C) @ 1 hour
All Fire Current:	800 mA
No Fire Current:	200 mA @ 5 minutes
ESD Pin to Pin:	25 KvDC @ 500 pF x 5 Kohm
ESD Pins to Case:	25 KvDC @ 500 pF
HIPOT Test Pins to Case:	5 kvDC@ 7 mA x 5 seg
Resistor:	2 x 27 Ohm @ 1/2 Watt resistors in series with bridge wire
Let to Leg Resistance:	60 ohm maximum

Shipping Information:

Proper Shipping Name:	Detonators, Electric, UN 0255, PGII, 1.4B
Part Number:	RJ-215
EX Number:	2002120146A
Quantity:	50 Units per case
Size:	14 x 14 x 7" (358 x 358 x 185 mm)
Gross Weight:	4.85 lb (2.20 kg)
Net Weight:	.88 lb (0.4 kg)
Net Explosive Content:	0.03 kg/box (0.0006 kg/unit)



ELECTRIC DETONA
PN: DET-E-L
LOT: RJC-***
DATE: *****
4789078001900
www.rjc.com.br

Please be sure to read, understand and follow all safety directions before handling this product. These types of detonators are designed to detonate when a small amount of electrical current is applied. Side initiating is not recommended with this product. Petro-Explo, Inc. is not responsible for any damages done by mishandling of this or any of our products. Please follow the Do's and Don'ts that are located in the top of box.

Petro-Explo, Inc • 7650 US Hwy 287 #100 Arlington TX 76001 • P 817-478-8888 800-588-8282 • PetroExplo.com • info@petroexplo.com

The product specifications above are for informational purposes only. For more detailed information contact us at the number above or by email. You can download the SDS from PetroExplo.com